

GX G-300™

NEW *from* Gendex!



The Simple Tool For Patient Education.

- Maximum Portability
- Advanced Technology
- Improved Performance

Cone Beam 3-D Imaging Systems

Panoramic X-ray Systems

Intraoral X-ray Systems

Digital Intraoral Sensors

Digital X-ray Phosphor Plates

➤ Intraoral Cameras

Imaging Software

GENDEX®
Imaging Excellence Since 1893



Featuring a high-speed direct USB 2.0 connection to eliminate the need for any type of docking station



Easily adjustable focus for intraoral and extraoral use



Convenient side capture button for image acquisition

Introducing the GXC-300

Gendex continues their long tradition of providing dental professionals with quality imaging equipment with our brand new, GXC-300 lightweight intraoral camera. Combining the latest video technologies, the GXC-300 is an exceptional tool for patient education, higher case acceptance, and improved patient communication.

➤ Maximum Portability

- High-speed direct USB connection with no docking station required
- Features a lightweight handpiece and reduced cabling
- Disconnects effortlessly for quick transfer to another operator

➤ Advanced Technology

- Virtually eliminates image distortion by utilizing true optics
- Sliding adjustable focus button for maximum performance
- Side capture button allows for Quad-Image capture
- Advanced 4 LED lighting system

➤ Improved Performance

- Camera activation controlled automatically by holster and always-active software interface
- Holster can be mounted almost anywhere so it's always within reach



GXC-300 Technical Specifications

Image Types	Intraoral and Extraoral Views / Freeze Quad-Image / Streaming Video
Angle of View	60°
Direction of View	90°
Focal Range	1 mm to infinity
Focus	Adjustable for Intraoral / Extraoral
Output Resolution	640 x 480 pixels
Lighting	4 High Luminance LEDs
USB Cable Length	3 meters (10 feet)
Dimensions	28.5 x 25.5 x 230 mm (1.1" x 1" x 9")
Weight	180 g

GXC-300 Minimum System Requirements

Operating System	Microsoft® Windows® XP SP2 or higher
Processor	Pentium® 4, 2 GHz or higher
Memory	1 GB
Video RAM	32 MB
Display Settings	1024 x 768 at 24 bit true color or higher
API	Microsoft® DirectX 9.0b or higher
Disk Drive	CD-ROM (for installation)
Ports	USB 2.0

KaVo Dental – Gendex Imaging
Via Alessandro Manzoni, 44
20095 Cusano Milanino
Milan, Italy
Tel. +39 02 618008.1
Fax +39 02 618008.09
www.gendex-dental.com
www.kavo.com

Manufactured by:
Gendex Dental Systems
901 W. Oakton Street
Des Plaines, IL 60018 USA

GENDEX
Imaging Excellence Since 1893